

		Cu7xx	
V i d e o	Video Compression Standard	ITU-H.263	
	Display	5" TFT LCD	
	Picture Resolution	CIF 352×288 pixels	
		QCIF 176×144 pixels	
		SQCIF 128×96 pixels	
	Frame Rate	CIF mode max. 30fps	
	Video camera	250K pixels CCD module	
External Video	NTSC/PAL Format		
A u d i o	Audio Compression Standard	G.711,G723.1,G729	
	Frequency Response	50Hz-3.4KHz	
	Audio Input	Handset/Hand-free microphone or External Audio source	
	Audio Output	Handset/Hand-free speaker or External Audio Equipment (RCA phono)	
	Audio Quality Control	Automatic Gain Control (AGC) Automatic Echo Cancellation	
S y s t e m F e a t u r e s	System Protocol	ITU-T standardH.323v2	
	Network	IP Network	
		Internet Local Area Network	
		Wide Area Network	
		Optional Network (Media converter required)	
	Picture Display Modes	3 Mode Selectable	
		Remote/Local/Both	
	Auto Answering	Yes	
	Audio/Video Auxiliary output	Yes	
External Equipment TV, Display monitor audio equipment			
Dimension(mm)	width, High, depth:		
	'9.1"×8.6"×3.2"		
	(23.0×21.8×8.1cm)		
	Weight:3.1 lbs(1.4kg)		
Environment	operating Temperature:32 to 113°F(0 to		
	Storage Temperature:-4 to 185°F(-20 to		
Humidity	Operating:15 % to 80 %		
	Storage:10 % to 90 %		
Power	Max.20 Watts		
	Operating Voltage 90-260VAC,50/60Hz		
Hands Free Speakerphone	Volume Adjustable		
Display Control	Adjustable Contrast, Brightness and Color		
Auxiliary Video Input	External Camera		
Auxiliary Video	TV Display or VCR		
Friendly User Interface	Redial, Mute, Flash (PSTN only)		
	Privacy, Snapshot, View (3 mode)		
	Handsfree/Handset, Volume, Setting		
	Phonebook		